





Routing Indices For Peer-to-Peer Systems

**presented by
Wei Xie
University of Toronto**



Outline

- ✦ **Introduction to Peer-to-Peer System**
- ✦ **Routing Indices**
- ✦ **Cycles in Peer-to-Peer Network**
- ✦ **Parallel Alternative of Routing Indices**
- ✦ **Conclusion**

Peer-to-Peer System

- Formed by a large number of nodes that can join or leave the system at any time
- Distributed computing nodes of equal roles or capabilities exchange information directly with each other

Famous P2P Systems

- Napster
- Gnutella
- Freenet
- GIOSS

Mechanism of Searching in P2P system

- mechanisms without an index
 - flooding network with queries
- mechanism with specialized index node
 - index node becomes bottleneck
- mechanism with indices at each node
 - routing indices
- mechanism with super nodes
 - every node stores metadata about its neighbors within depth n

Routing Indices

Select the best neighbors to send query to

Key factor is how to define and compute the goodness suitable to a specific query

- Compound Routing Index (CRI)
- Hop-count Routing Index (HRI)
- Exponentially Aggregated Routing Index (ERI)




Figure 4. Routing Indices

Compound RI

- summary of detailed index
- compact data structure
- goodness= the number of documents that could be found in a path
- send query in depth-first fashion
- savings in the number of messages
- modest storage space
- introduce errors of overcount or undercount

$$\text{Number of Documents} \times \prod_i \frac{CRI(u_i)}{\text{Number of Documents}}$$

- maintenance?
- effect of errors?

Path	# docs	Documents with topic
		DB N T L
E	100	30 0 10 10
G	1000	0 300 0 10
D	200	100 0 100 100




Figure 3. A Sample Compound RI

Hop-count RI

- take into account of numbers of hops
- **regular-tree model** to compute goodness
- need local network structure to decide value of **horizon**
- higher storage and transmission cost
- potential loss in accuracy
- complicated maintenance algorithm

$$goodness_{hc}(Neighbor_i, Q) = \sum_{j=0, \dots, h} \frac{goodness(N_j, L, Q)}{j^{j+1}}$$

Node	1 Hop					2 Hops				
	#	DB	N	T	L	#	DB	N	T	L
X	40	13	2	8	10	20	50	10	4	17
Y	20	0	3	18	12	80	31	0	25	20
Z	8	2	0	8	3	70	50	40	30	80





Figure 6. A sample Hop-count RI for node W

Exponential RI

- keep info. for **all** nodes accessible from each path
- dynamic data structure
- need complete information of local network
- unrealistic assumptions of regular tree model



Regular Tree

Path	#	DB	N	T	L
X	66.67	16.55	5.33	6.33	15.67
Y	46.67	10.55	5.00	20.00	18.67
Z	28.33	5.55	18.33	9.67	19.67




Figure 7. A sample Exponential Routing Index for Node W

Algorithms for creating/update RI, answering queries

```

RI Creation/Update Algorithm
Input:  $I$ 
Output: An updated RI (as a side effect)

// Creation phase
 $RI[0] = Summary(I)$ 
For each neighbor  $j$ :
     $Send(j, RI[0])$ 

// Update phase
 $OldRI = RI$ 
While (true):
    Wait for a batch of aggregated RIs to arrive and/or
    for the local index to change
    For each aggregated RI (if any),  $A_k$ , received from neighbor  $k$ :
         $RI[k] = A_k$ 
    If local index changed:
         $RI[0] = Summary(I)$ 
    If  $OldRI$  is different enough than  $RI$ :
         $OldRI = RI$ 
        For each neighbor  $j$  in  $RI$ :
             $A = Aggregate(RI[0..j-1, j+1..N])$ 
             $Send(j, A)$ 
    
```

```

Answer Query
Input: A query  $Q$ , a client  $C$ , and a node  $F$ 
Output: Query answers; Query forwards

Send local answers for  $Q$  to  $C$ 
If StopCondition():
    return
 $Rank = []$ 
For each neighbor  $j$  except  $F$ :
     $Rank.Append(j, Estimator(RI[j])(Q))$ 
    Sort tuples in  $Rank$  by second attribute
for  $i$  in  $Rank$ :
    Send query to neighbor  $i[0]$ 
    If StopCondition():
        return
    
```

Figure 7: RI Usage Algorithm

Effect of errors

assumption:

- documents are organized into categories
- index is hash table of categories

results show:

- loss is modest
- similar results to undercounts and mixed errors




Figure 13: Effect of Overcounts

Cycles in the P2P System




Figure 8: Cycles and Routing Indices




Figure 10: Effect of Cycles

- ✦ No-op
- ✦ Cycle avoidance
- ✦ Cycle detection and recovery

- ✦ signature: unique message id
- ✦ ignore some update messages

Performance Evaluation

Topology

- Tree
- Tree with added cycles
- Power-law graph




Figure 18: Updates and Network Topology

Data Distribution

- Uniform
- 80/20





Figure 10: Comparison of CRI, HRI, and ERI

Parallel Alternative of Routing Indices

```
for each node  $i$  in data structure  
if  $|goodness_{highest} - goodness_i| \leq threshold$   
{  
    send  $Q$  to node  $i$   
    apply RI algorithm  
}
```


- **threshold** represents the possibility similarity of finding results in different paths
- value of **threshold** is decided by many factors:
 - number of results (stop condition)
 - response time limitation



Better response time!

Conclusion

- ◆ Propose simple and effective strategies
- ◆ Compact data structures and algorithms
- ◆ Do not need to know global network architecture
- ◆ Reduce the number of messages greatly
- ◆ Sequential algorithms, but can be changed to parallel ones easily
- ◆ Response time is worse than non-index systems
- ◆ Paper is easy to understand



Thanks for your patience!

Happy Halloween!